DESIGN NOTES

- Design is based on the assumption that backfill within the reinforced soil mass, methods of construction and quality of materials conform to the requirements of Hilfiker Retaining Walls.
- 2. Assumed Soil Characteristics:

Wall Backfill:

Unit Weight: 130 pcf Internal Friction Angle: 36°

Cohesion = 0 psf

Retained Backfill:

Unit Weight: 125 pcf

Internal Friction Angle: 34° Cohesion = 0 psf

Foundation Soils:

Unit Weight: 130 pcf

Friction Angle for Sliding: 36°

Cohesion = 0 psf

Applied Bearing Pressure - applied at 37' Height - Factor Bearing Load - 9.736 psf.

- in actual characteristics, grades or dimensions or soil materials differ from those listed above or shown on the plans, Hilfiker Retaining walls shall be notified to evaluate the need to redesign.
- If during construction, the wall location, structure location or loads are different than that proposed in this plan set and calculation package, HRW shall be notified to evaluate the need for a redesign.
- The design requires a non-saturated backfill. Surface and sub-surface drainage control may be required to prevent saturation of the backfill or relieve hydrostatic pressures.
- Design Procedure: Mechanically Stabilized Earth walls and Reinforced Soil Slopes, FHWA report No. FHWA-NHI-00-044.


- 6. All information hereon is derived from the reference drawings, and is subject to geometric and geotechnical confirmation. The applicable Hilfiker construction guide and specifications are an integral part of this submittal.
- 7. Internal stability of the retaining wall as well as global stability and foundation bearing capacity was evaluated. The Contractor is responsible for all job site drainage, safety and fall protection provisions for workers in compliance with OSHA and any other applicable requirements.
 Note: If Foundation Soils are soft and/or yielding, removal of this material and replacing with acceptable engineered fill is

PROPOSED QUANTITIES:

 $\begin{array}{ll} \underline{\mathsf{MSE}\;\mathsf{WALL}\;\mathsf{AREA:}} \\ \underline{\mathsf{MSE}\;\mathsf{WALL}\;\mathsf{STA}\;37+90} \\ \underline{\mathsf{MSE}\;\mathsf{WALL}\;\mathsf{STA}\;46+93} \\ \end{array} \qquad \begin{array}{ll} 2,012\;\mathsf{FT}^2 \\ 3,768\;\mathsf{FT}^2 \end{array}$

5,780 FT²

TOTAL WALL AREA:



THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE CONTRACTOR. ON THE BASIS OF THIS INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE. EXTERNAL STABILITY HAS BEEN REVIEWED AND THE BEARING CAPACITY OF THE FOUNDATION HAS BEEN EVALUATED. IF DURING CONSTRUCTION AND EXPOSURE THE FOUNDATION MATERIAL IS FOUND TO BE SUSPECT, THE ROGINEER SHALL BE INFORMED IMMEDIATELY FOR CONSULTATION.

| REV.NO. | DATE | BY | DESCRIPTION |
|---------|-----------|-----|--|
| | 06/16/ 17 | KLC | Intial Soft .pdf Release |
| | 07/26/17 | KLC | Revised Per Plan Check Comments 7/ 7/ 17 |
| | 01/17/18 | KLC | Revised Per Plan Check Comments 10/30/17 |
| | 04/30/18 | KLC | Revised Deicing Membrane Geometry Per Plan |
| | | | Check Comments 10/30/17 |
| | | | |

HILFIKER RETAINING WALLS



1902 Hilfiker Lane Eureka, CA 95503-5711 TOLL-FREE **800.762.8962** PH **707.443.5093** FAX **707.443.2891**



SCALE: 1"= 20'


CESARETTI
Engineered
Solutions
CIVIL ENGINEERING SPECIALISTS

P.O. Box 132 Fortuna, CA 95540 Phone (707) 725-CESR (707) 498-7193 CesarettiEngineered.com KCesaretti@att.net S FORK FLATHEAD - HUNGRY HORSE WELDED WIRE & RSE MSE WALLS

MSE WALL BENT 1 PLAN VIEW & GENERAL NOTES

| , | LCC. | |
|---|---------|----------|
| | HW 17 | 70330EW |
| | PROJECT | 17-022 |
| | DATE | 06-16-17 |
| | DESIGN | KLC |
| | DRAWN | KLC |

SHT 1 OF



MSE WALL STA 38+42 - ELEVATION VIEW - REAR VIEW

WALL WIRE TYPE LEGEND

FINISH: HOT DIP GALVANIZED SERVICE LIFE: 75 YEARS

TYPE 1 - 8x12 W7.0x3.5 MATS

TYPE 1 CLOSURE MAT- 8x12 W7.0x3.5 MATS

TYPE 2 - 8x21 W7.0x4.0 MATS TYPE 3 - 8x21 W9.5x4.0 MATS

| WELDED WIRE WALL PARAMETERS | | | | | |
|-----------------------------|---|--------------------------------|--|--|--|
| Height of Wall (H) | Length of Cap & Prongless Mats (B1) | Length of Standard Mats (B) | | | |
| 12'-14' | 12.0' | 12.25' | | | |
| 16' | 13.0' | 14.0' | | | |
| 18' | 15.0' | 15.75' | | | |
| 20'-21' | 16.0' | 17.5' | | | |
| 24' | 20.0' | 19.25' | | | |
| 34' | 28.0' | 28.0' | | | |
| 36' | 29.0' | 29.75' | | | |

Cap & Prongless Mats are: 8x12 W7.0x3.5 WWR (Type 1) 8x21 W7.0x4.0 WWR (Type 2) Standard Mats are: 8x21 W9.5x4.0 WWR (Type 3)

Finish: HOT DIP Galvanized - 75 Year Service Life



| 7 | REV.NO. | DATE | BY | DESCRIPTION |
|------|---------|-----------|-----|--|
| olde | | 06/16/ 17 | KLC | Intial Soft .pdf Release |
| ш. | | 07/26/17 | KLC | Revised Per Plan Check Comments 7/ 7/ 17 |
| Fie | | 01/17/18 | KLC | Revised Per Plan Check Comments 10/30/17 |
| era | | | | |
| Gen | | | | |
| ပ် | | | | |

HILFIKER RETAINING WALLS



SCALE: 1" = 10'

1902 Hilfiker Lane Eureka, CA 95503-5711 TOLL-FREE **800.762.8962** PH 707.443.5093 FAX 707.443.2891




CESARETTI Engineered Solutions CIVIL ENGINEERING SPECIALISTS

P.O. Box 132 Fortuna, CA 95540 Phone (707) 725-CESR (707) 498-7193 CesarettiEngineered.com KCesaretti@att.net

S FORK FLATHEAD - HUNGRY HORSE WELDED WIRE MSE WALLS

BENT 1 ELEVATION VIEW

| HW 1 | 70330EW |
|---------|----------|
| PROJECT | 17-022 |
| DATE | 06-16-17 |
| DESIGN | KLC |
| DRAWN | KLC |
| | |
| | |



THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE CONTRACTOR. ON THE BASIS OF THIS INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE. EXTERNAL STABILITY HAS BEEN REVIEWED AND THE BEARING CAPACITY OF THE FOUNDATION HAS BEEN EVALUATED. IF DURING CONSTRUCTION AND EXPOSURE THE FOUNDATION MATERIAL IS FOUND TO BE SUSPECT, THE ENGINEER SHALL BE INFORMED IMMEDIATELY FOR CONSULTATION.

| REV.NO. | DATE | BY | DESCRIPTION |
|---------|-----------|-----|--|
| | 06/16/ 17 | KLC | Intial Soft .pdf Release |
| | 07/26/17 | KLC | Revised Per Plan Check Comments 7/ 7/ 17 |
| | 01/17/18 | KLC | Revised Per Plan Check Comments 10/30/17 |
| | 04/30/18 | KLC | Revised Deicing Membrane Geometry Per Plan |
| | | | Check Comments 10/30/17 |
| | | | |

HILFIKER RETAINING WALLS



1902 Hilfiker Lane
Eureka, CA 95503-5711
TOLL-REE 800.762.8962
PH 707.443.5093 FAX 707.443.2891






P.O. Box 132 Fortuna, CA 95540 Phone (707) 725-CESR (707) 498-7193 CesarettiEngineered.com KCesaretti@att.net


S FORK FLATHEAD - HUNGRY HORSE WELDED WIRE MSE WALLS

MSE WALL BENT 5 PLAN VIEW


| | 1111111 | | | | | | |
|---|---------|---------|--|--|--|--|--|
| | HW 1 | 70330EW | | | | | |
| | PROJECT | 17-022 | | | | | |
| : | DATE | 06-16- | | | | | |
| - | DESIGN | KLC | | | | | |
| | DRAWN | KLC | | | | | |
| | | | | | | | |
| | | | | | | | |

SHT 3 OF 9






CUT THE TRANSVERSE WIRES ON THE BASE OF THE MATS AND BEND THE FACE OF THE MATS TO THE REQUIRED ANGLE. OVERLAP THE BASE



PLAN VIEW OBTUSE CONVEX ANGLE NOT TO SCALE



PLAN VIEW CONCAVE ANGLE DETAIL NOT TO SCALE



BY DESCRIPTION 06/16/ 17 KLC Intial Soft .pdf Release 07/26/17 KLC | Revised Per Plan Check Comments 7/ 7/ 17 KLC Revised Per Plan Check Comments 10/30/17 01/17/18 KLC Revised Per Plan Check Comments 1/30/18 03/17/18 KLC Revised Deicing Membrane Geometry Per Plan 04/30/18

Check Comments 10/30/17

THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE CONTRACTOR. ON THE BASIS OF THIS INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS

RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE EXTERNAL STABILITY HAS BEEN REVIEWED AND THE BEARING CAPACITY OF THE FOUNDATION HAS BEEN EVALUATED. IF DURING CONSTRUCTION

AND EXPOSURE THE FOUNDATION MATERIAL IS FOUND TO BE SUSPECT THE ENGINEER SHALL BE INFORMED IMMEDIATELY FOR CONSULTATION

Many Department of Transportations use de-icing salts in the winter months to provide safer roadways. Metallic reinforcing if exposed to these salts are at risk to higher corrosion rates and loss of service life. To protect the Steel reinforcing in MSE walls it is an acceptable practice to use an impervious barrier around the reinforcing and a drainage system design that diverts the salts and protects the reinforcing.

HILFIKER RETAINING WALLS



1902 Hilfiker Lane Eureka, CA 95503-5711 TOLL-FREE 800.762.8962 PH 707.443.5093 FAX 707.443.2891 WEB SITE www.hilfiker.com E-MAIL info@hilfiker.com





P.O. Box 132 Fortuna, CA 95540 Phone (707) 725-CESR (707) 498-7193 CesarettiEngineered.com KCesaretti@att.net

S FORK FLATHEAD - HUNGRY HORSE WELDED WIRE MSE WALLS

ERS CROSS SECTION VIEW & AP DETAIL

| HVV 1 | 70330EVV |
|---------|---------------------------|
| PROJECT | 17-022 |
| DATE | 06-16-17 |
| DESIGN | KLC |
| DRAWN | KLC |
| | |
| | PROJECT DATE DESIGN |


SHT **5** OF **9**




PLACE THE FIRST COURSE OF SOIL REINFORCEMENT MATS ON PREPARED FOUNDATION



STEP 2



STEP 3



STEP 4


HOOK THE BOTTOM TRANSVERSE WIRE OF THE BACKING MAT OVER THE VERTICAL PRONGS ON THE LOWER MAT. ROTATE THE BACKING MAT TO VERTICAL AND CLIP THE SECOND-TO-TOP TRANSVERSE WIRE ON THE BACKING TOP WIRE ON MAT TO THE TOP WIRE ON THE SOIL REINFORCEMENT BACKING MAT FIRST COURSE

STEP 5

INSTALL FILTER FABRIC BEHIND THE BACKING MATS.

PLACE AND COMPACT THE BACKFILL TO THE BASE ELEVATION OF THE NEXT MAT.

REPEAT STEPS 3 THRU 5 TO THE TOP LIFT.



PLACE THE TOP LIFT PRONGLESS MAT, BACKING MAT AND FILTER FABRIC.

CUT OFF HEIGHT OF PRONGLESS MAT FACE AND FILTER FABRIC, IF REQUIRED, TO PARALLEL


PLACE AND COMPACT THE BACKFILL IN THE PRONGLESS MAT LIFT.

ERS MSE WALL CONSTRUCTION SEQUENCE NOT TO SCALE

CAP MAT FILL AND COMPACT VOID ANCHORAGE TOP LIFT HEIGHT MAY VARY CAP MAT **PRONGLESS** LEVELING COURSE STEP 7

INSTALL THE CAP MAT OVER THE COMPACTED BACKFILL. INSTALL THE PANEL ANCHORAGES TO THE SPACING SHOWN IN THE PROJECT PLANS. BACKFILL TO 1'-6" MINIMUM COVER OVER THE TOP MAT.

BACKFILL AT THE TOE TO THE ELEVATION OF THE BOTTOM OF THE LEVELING COURSE. FORM THE LEVELING COURSE WITH KEYWAY, AS SHOWN IN THE CLOSURE MAT PROJECT PLANS



PLACE THE BOTTOM OF THE PRECAST FULL-HEIGHT PANEL INTO THE KEYWAY ON THE LEVELING COURSE. RAISE THE PANEL TO VERTICAL AND ATTACH TO THE PANEL ANCHORAGE.

PUSH PRONGS OF THE CLOSURE MAT INTO SOIL BEHIND THE BEND IN THE TOP MAT AND ROTATE TOP OF THE CLOSURE MAT FORWARD UNTIL IT CONTACTS THE BACK OF THE PANEL. PLACE BACKING MATS AND FILTER FABRIC BEHIND CLOSURE MATS AND BACKFILL

BACKFILL AT TOE TO FINAL GRADE. FINISH THE TOP OF THE WALL PER PROJECT PLANS.

ONAL

| THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON |
|---|
| INFORMATION PROVIDED BY THE CONTRACTOR. ON THE BASIS OF THIS |
| INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS |
| RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE. |
| EXTERNAL STABILITY HAS BEEN REVIEWED AND THE BEARING CAPACITY |
| OF THE FOUNDATION HAS BEEN EVALUATED. IF DURING CONSTRUCTION |
| AND EXPOSURE THE FOUNDATION MATERIAL IS FOUND TO BE SUSPECT, |
| THE ENGINEER SHALL BE INFORMED IMMEDIATELY FOR CONSULTATION. |
| |

| REV.NO. | DATE | BY | DESCRIPTION |
|---------|-----------|-----|--|
| olde | 06/16/ 17 | KLC | Intial Soft .pdf Release |
| 0 | 07/26/17 | KLC | Revised Per Plan Check Comments 7/7/17 |
| Ē | 01/17/18 | KLC | Revised Per Plan Check Comments 10/30/17 |
| erd | | | |
| e J | | | |
| ပ် | | | |

HILFIKER RETAINING WALLS



1902 Hilfiker Lane Eureka, CA 95503-5711 TOLL-FREE 800.762.8962 PH 707.443.5093 FAX 707.443.2891 WEB SITE www.hilfiker.com E-MAIL info@hilfiker.com







P.O. Box 132 Fortuna, CA 95540 Phone (707) 725-CESR (707) 498-7193 CesarettiEngineered.com KCesaretti@att.net

S FORK FLATHEAD - HUNGRY HORSE WELDED WIRE MSE WALLS **ERS CONSTRUCTION SEQUENCE &** DETAILS

| HW 1 | 170330EW |
|---------|----------|
| PROJEC* | т 17-022 |
| DATE | 06-16-17 |
| DESIGN | KLC |
| DRAWN | KLC |
| | • |
| SHT | 6 6 |






SECTION GUARDRAIL DETAIL

NOT TO SCALE (FENCE DETAIL SIMILAR)

MAT AND CONTINUOUS HEEL OF MAT COVER OVER CAP MAT 8"x12" WWF CAP MAT PRECAST FULL-HEIGHT 8"x12" WWF PANELS, TOP LIFT MAT (BY OTHERS) COMPACTED WALL BACKFILL 8"x21" STANDARD WELDED WIRE SOIL REINFORCEMENT WELDED WIRE BACKING MAT AND CONTINUOUS FILTER
FABRIC BEHIND MAT FACES - 8" SPACE BETWEEN MATS **ERS PICTORIAL ELEVATION** 3"- 4" Anchor is Precision Buried **Protrusion During Placement of Backfill** Face of Welded Wire Wall

8"x12" WWF CLOSURE MAT, BACKING



THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE CONTRACTOR. ON THE BASIS OF THIS INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE. EXTERNAL STABILITY HAS BEEN REVIEWED AND THE BEARING CAPACITY OF THE FOUNDATION HAS BEEN EVALUATED. IF DURING CONSTRUCTION AND EXPOSURE THE FOUNDATION MATERIAL IS FOUND TO BE SUSPECT, THE ENGINEER SHALL BE INFORMED IMMEDIATELY FOR CONSULTATION.

| - | REV.NO. | DATE | BY | DESCRIPTION |
|---------|---------|-----------|-----|--|
| olde | | 06/16/ 17 | KLC | Intial Soft .pdf Release |
| - | | 07/26/17 | KLC | Revised Per Plan Check Comments 7/ 7/ 17 |
| File | | 01/17/18 | KLC | Revised Per Plan Check Comments 10/30/17 |
| General | | | | |
| Ger | | | | |
| - 6 | | | | |

HILFIKER RETAINING WALLS



1902 Hilfiker Lane
Eureka, CA 95503-5711
TOLL-FREE 800.762.8962
PH 707.443.5093 FAX 707.443.2891
WEB SITE www.hilfiker.com E-MAIL info@hilfiker.com






P.O. Box 132 Fortuna, CA 95540 Phone (707) 725-CESR (707) 498-7193 CesarettiEngineered.com KCesaretti@att.net

S FORK FLATHEAD - HUNGRY HORSE ERS & WELDED WIRE WALL DETAILS

| HW 1 | 70330E | W |
|---------|-------------|------|
| PROJECT | 17-022 | |
| DATE | 06-1 | 6-17 |
| DESIGN | KLC | |
| DRAWN | KLC | |
| | | |
| SHT | 7 of | 9 |

MAL



PANEL ANCHORAGE COMPONENTS

PRECAST PANEL CONNECTION BRACKET NOT TO SCALE

SIDE VIEW

THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE CONTRACTOR. ON THE BASIS OF THIS INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE. EXTERNAL STABILITY HAS BEEN REVIEWED AND THE BEARING CAPACITY OF THE FOUNDATION HAS BEEN REVIEWED AND THE BEARING CAPACITY OF THE FOUNDATION HAS BEEN EVALUATED. IF DURING CONSTRUCTION AND EXPOSURE THE FOUNDATION MATERIAL IS FOUND TO BE SUSPECT, THE ENGINEER SHALL BE INFORMED IMMEDIATELY FOR CONSULTATION.

1/2" R

| REV.NO. | DATE | BY | DESCRIPTION |
|---------|-----------|-----|--|
| | 06/16/ 17 | KLC | Intial Soft .pdf Release |
| | 07/26/17 | KLC | Revised Per Plan Check Comments 7/7/17 |
| | 01/17/18 | KLC | Revised Per Plan Check Comments 10/30/17 |
| | | | |
| | | | |

FRONT VIEW

HILFIKER RETAINING WALLS



DRAIN HOLE

1902 Hilfiker Lane
Eureka, CA 95503-5711
TOLL-FREE 800.762.8962
PH 707.443.5093 FAX 707.443.2891
WEB SITE www.hilfiker.com E-MAIL info@hilfiker.com



ESARETTI
Engineered
Solutions
CIVIL ENGINEERING SPECIALISTS

P.O. Box 132 Fortuna, CA 95540 Phone (707) 725-CESR (707) 498-7193 CesarettiEngineered.com KCesaretti@att.net

S FORK FLATHEAD - HUNGRY HORSE
PANEL ANCHOR
DETAILS

| HW 170330EW | | | | | |
|-------------|--------------|----------|--|--|--|
| | PROJECT 1 | 7-022 | | | |
| | DATE | 06-16-17 | | | |
| | DESIGN | KLC | | | |
| | DRAWN | KLC | | | |
| | sнт 8 | of 9 | | | |

ONAL

CONC ANCHOR BLOCK OR 3/8"

3/4" HEX NUT AND

WASHER, EACH SIDE

PLATE (ASTM A36), 10" SQUARE

