DESIGN NOTES

- Design is based on the assumption that backfill within the reinforced soil mass, methods of construction and quality of materials conform to the requirements of Hilfiker Retaining Walls.
- 2. Assumed Soil Characteristics:

Wall Backfill:

Unit Weight: 120 pcf Internal Friction Angle: 34°

Cohesion = 0 psf

Retained Backfill:

Unit Weight: 120 pcf

Internal Friction Angle: 34°

Cohesion = 0 psf

Foundation Soils:

Unit Weight: 120 pcf

Friction Angle for Sliding: 34°

Cohesion = 0 psf

Applied Bearing Pressure (@ 20' High Section) - 3100 psf

If actual characteristics, grades or dimensions of soil materials differ from those listed above or shown on the plans, Hilfiker Retaining walls shall be notified to evaluate the need to redesign.

- 3. If during construction, the wall location, structure location or loads are different than that proposed in this plan set and calculation package, HRW shall be notified to evaluate the need for a redesign.
- 4. The design requires a non-saturated backfill. Surface and sub-surface drainage control may be required to prevent saturation of the backfill or relieve hydrostatic pressures.

Drainage control shall be as specified in the project plans and specifications or as directed by the engineer.

5. Design Procedure: Mechanically Stabilized Earth walls and Reinforced Soil Slopes, FHWA report No. FHWA-NHI-00-043.

6. All information hereon is derived from the reference drawings, and is subject to geometric and geotechnical confirmation. The applicable Hilfiker construction guide and specifications are an integral part of this submittal.


Reference Documents:

Civil Plans - By AECOM, Tualatin Valley Water District, Proj. No. 60273015, Dated June 1014.

7. Hilfiker Retaining Walls shall be responsible only for the internal stability of the retaining wall, and not for global stability or foundation bearing capacity. The owner/contractor shall be responsible for all job site drainage, safety and fall protection provisions for workers in compliance with OSHA and any other applicable requirements.

INSIDE STAIR WALL AREA: 256 SF **OUTSIDE STAIR WALL AREA:** 672 SF L303 WALL: 1,240 SF L302 WALL: 808 SF TOTAL SUPPLIED QTY: 2,976 SF

SUPPLIED QUANTITIES:



THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE OWNER. ON THE BASIS OF THIS INFORMATION. THE HILFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE ONLY. EXTERNAL STABILITY, INCLUDING FOUNDATION AND SLOPE STABILITY, IS THE RESPONSIBILITY OF THE OWNER

DESCRIPTION 11-5-14 KLC | Soft Copy .pdf Release 11-12-15 KLC | Modified per Plan Check Comments 12-21-15 KLC Added Notation concerning the Added Sheet 6

HILFIKER RETAINING WALLS



1902 Hilfiker Lane Eureka, CA 95503-5711 TOLL-FREE **800.762.8962** PH 707.443.5093 FAX 707.443.2891 WEB SITE www.hilfiker.com E-MAIL_info@hilfiker.com






167 S. Fortuna Blvd. Fortuna, CA 95540 Phone (707) 725-7410 Fax (707) 725-7411 Ontiveros.Assoc@att.net RIDGEWOOD VIEW PARK RESERVOIR & PUMP STATION PORTLAND, OR

MSE PLAN VIEW & GENERAL NOTES

HW 130829AG PROJECT 14-110 DATE 11-5-14 DESIGN KLC DRAWN KLC



WELDED WIRE WALL PARAMETERS							
Height Length of Cap & Prongless Mats		Base Length of Mats					
(H) ft	(B₁) ft	(B ₂) ft					
<u><</u> 12' 14'	9'	8.75'					
16'	9' 9'	8.75 & 10.5' 8.75' & 12.25'					
20'	9'	8.75' & 14'					

Cap & Top Mats (B1) are 8x12 W4.5x3.5 WWR (Type 1) Standard Mats (B2) are 8x10.5 W4.5x3.5 WWR (Type 2) & are also 8x10.5 W7.0x3.5 WWR (Type 3) where shown.

Finish: Hot Dip Galvanized - 75 Year Service Life

WALL WIRE TYPE LEGEND

FINISH: HOT DIPPED GALVANIZED SERVICE LIFE: 75 YEARS

TYPE 1 - 8x12 W4.5x3.5 MATS
TYPE 2 - 8x10.5 W4.5x3.5 MATS

TYPE 3 - 8x10.5 W7.0x3.5 MATS


BEGIN WALL WLOL 30+00 END WALL WLOL 31+28 128' OF WELDED WIRE WALL - 1:48 Batter 24' 44' 12' 16' 16' H = 6.0' 8.0' 3.0' 4.0' 5.0' 7.0' B₁ = 9.0' 9.0' 9.0' 9.0' 9.0' 9.0' $B_2 =$ 8.75' 8.75' 8.75' 8.75' 8.75' 8.75' TOP OF WALL BOTTOM SEE SLOPE CAP OF WALL **DETAIL SHT 4**


ELEVATION VIEW OF OUTSIDE STAIR WALL

SCALE: 1" = 20'

ELEVATION VIEW OF L302 WALL

SCALE: 1" = 20'





ELEVATION VIEW OF INSIDE STAIR WALL

SCALE: 1" = 20'

HW 130829AG

THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE OWNER. ON THE BASIS OF THIS INFORMATION, THE HILLFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE ONLY. EXTERNAL STABILITY, INCLUDING FOUNDATION AND SLOPE

STABILITY, IS THE RESPONSIBILITY OF THE OWNER

REV.NO. DATE BY DESCRIPTION

11-5-14 KLC Soft Copy .pdf Release

11-12-15 KLC Modified per Plan Check Comments

HILFIKER RETAINING WALLS







167 S. Fortuna Blvd. Fortuna, CA 95540 Phone (707) 725-7410 Fax (707) 725-7411 Ontiveros.Assoc@att.net RIDGEWOOD VIEW PARK RESERVOIR & PUMP STATION PORTLAND, OR

MSE ELEVATION VIEW

!	100 130	UZJA	<u> </u>
	PROJECT	14-11	0
	DATE	11-5-1	4
	DESIGN	KLC	
	DRAWN	KLC	
		_	
		つ	_
	SHT	८ o	FϽ






FOR A SMOOTHER CURVE, SPLIT THE MAT BASES AND BEND THE FACES. DO NOT SPLIT MAT FACES FOR A SMOOTHER CURVE SPLIT OR CUT LONGITUDINAL WIRES THE MAT BASES AND BEND THE FACES. DO NOT SPLIT MAT FACES OR CUT LONGITUDINAL BACK OF THE WELDED WIRE WALL MATS WELDED WIRE WALL FACE TOP OF BERM SPREAD THE BACK OF THE TOP OF BERM MATS PLAN VIEW **CONCAVE CURVE**


NOT TO SCALE

PLAN VIEW CONVEX CURVE

CLOSE END OF WALL AT APPURTENANCE AS SHOWN IN "WELDED WIRE WALL END AT APPURTENANCE" DETAIL, THIS SHEET



ELEVATION CULVERT THRU WALL FACE




STEP 4 PLACE AND COMPACT BACKFILL OVER THE SLOPED CAPS TO FINAL GRADE

PLACE CAPS ON SLOPE STEP 1 CUT OFF TOP OF THE MAT FACES, BACKING MATS, AND FILTER FABRIC OR CONTINUOUS HARDWARE CLOTH PARALLEL TO FINAL GRADE FACE OF WALL MAT FACES WITH HOG RINGS HORIZONTAL MATS **PICTORIAL ELEVATION**


PLAN VIEW

DEFLECTED LONGITUDINAL WIRES NOT TO SCALE

FITTING MATS TO OBSTRUCTION



SLOPED CAP MAT DETAIL NOT TO SCALE



REINFORCEMENT MAT CENTERLINE OF MAT FACE = EDGE OF BACKING MATS FILTER FABRIC BACKING AT EXPOSED END OF ALL TOP LIFTS, INSTALL BACKING MAT AND FILTER FACE OF WWF SOIL FABRIC AS SHOWN TO REINFORCEMENT MAT PREVENT LOSS OF BACKFILL

PLAN VIEW ANGLED PIPE PENETRATION NOT TO SCALE

THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE OWNER. ON THE BASIS OF THIS INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE ONLY. EXTERNAL STABILITY, INCLUDING FOUNDATION AND SLOPE STABILITY, IS THE RESPONSIBILITY OF THE OWNER

WELDED WIRE WALL END AT OTHER APPURTENANCE NOT TO SCALE

ISOMETRIC VIEW

BASE OF WWF SOIL

WELDED WIRE WALL COMPONENTS WITH RETURN MAT

NOT TO SCALE

ŀ	IW 130	829AG
		14-110
RIDGEWOOD VIEW PARK RESERVOIR		11-5-14
& PUMP STATION	DESIGN	KLC
ar own oration	DDAMAI	KI C

MSE DETAILS

e Folder\	REV.NO.	DATE	БТ	DESCRIPTION
		11-5-14	KLC	Soft Copy .pdf Release
		11-12-15	KLC	Modified per Plan Check Comments
茝				
eral				
Ger				

HILFIKER RETAINING WALLS


Eureka, CA 95503-5711 TOLL-FREE **800.762.8962** PH **707.443.5093** FAX **707.443.2891** WEB SITE www.hilfiker.com E-MAIL info@hilfiker.com





167 S. Fortuna Blvd. Fortuna, CA 95540 Phone (707) 725-7410 Fax (707) 725-7411

& PUMP PORTLAND, OR



STEP 3

BRING THE FILTER FABRIC OVER THE FRONT AND TOP OF THE BACKFILL AS SHOWN. PLACE THE ROCK IN THE FACE OF THE WALL. LEAVE A VOID AS SECOND COURSE SOIL REINFORCEMENT MAT PLACE THE SECOND COURSE OF SOIL REINFORCEMENT MATS WITH THE BASE LONGITUDINAL WIRES RESTING ON THE TOP TRANSVERSE WIRE OF THE BACKING MAT BELOW. SLIDE THE SOIL REINFORCEMENT MAT INTO ALIGNMENT. OLOVOID BACKING MAT HOOK THE BOTTOM TRANSVERSE WIRE OF THE BACKING MAT OVER THE VERTICAL PRONGS ON THE LOWER MAT. ROTATE THE BACKING MAT TO VERTICAL AND CLIP THE TOP WIRE ON SECOND-TO-TOP TRANSVERSE WIRE ON THE BACKING BACKING MAT MAT TO THE TOP WIRE ON THE SOIL REINFORCEMENT HÓG RING


CONSTRUCTION SEQUENCE

FIRST COURSE

NOT TO SCALE


STEP 5

INSTALL THE FILTER FABRIC AS IN STEPS 2 AND 3 AND THE BACKING MAT. PLACE AND COMPACT THE BACKFILL AND ROCK TO THE BASE ELEVATION OF THE NEXT MAT. REPEAT STEPS 2 THROUGH 5 TO THE TOP LIFT.



STEP 6: TOP LIFT

PLACE THE TOP LIFT PRONGLESS MAT AND BACKING MAT. PLACE AND COMPACT BACKFILL AND ROCK IN THE TOP LIFT. HOOK THE CAP OVER THE MIDDLE TRANSVERSE WIRE ON THE PRONGLESS MAT, AND ROTATE INTO PLACE. PLACE AND COMPACT COVER OVER TOP MAT TO 1'-6" MINIMUM DEPTH.



RETURN MATS AND TOP OF WALL DETAIL NOT TO SCALE

THE DESIGN CONTAINED ON THESE DRAWINGS IS BASED ON INFORMATION PROVIDED BY THE OWNER. ON THE BASIS OF THIS INFORMATION, THE HILFIKER COMPANY HAS DESIGNED, AND IS RESPONSIBLE FOR THE INTERNAL STABILITY OF THE STRUCTURE ONLY. EXTERNAL STABILITY, INCLUDING FOUNDATION AND SLOPE STABILITY, IS THE RESPONSIBILITY OF THE OWNER

DESCRIPTION KLC Soft Copy .pdf Release 11-12-15 KLC Modified per Plan Check Comments

HILFIKER RETAINING WALLS



Eureka, CA 95503-5711 TOLL-FREE **800.762.8962** PH 707.443.5093 FAX 707.443.2891 WEB SITE www.hilfiker.com E-MAIL info@hilfiker.com





167 S. Fortuna Blvd. Fortuna, CA 95540 Phone (707) 725-7410 Fax (707) 725-7411

RIDGEWOOD VIEW PARK RESERVOIR & PUMP STATION PORTLAND, OR

MSE DETAILS

HW 130829AG којест 14-110 DATE 11-5-14 DESIGN KLC DRAWN KLC